A-posteriori-steered and adaptive *p*-robust multigrid solvers

$\label{eq:main_stress} \begin{array}{c} \underline{\mathbf{Ani}\ \mathbf{Mira}\mathbf{\hat{c}i}^1}, \ \mathbf{Jan}\ \mathbf{Pape}\mathbf{\check{z}}^2, \ \mathbf{Dirk}\ \mathbf{Praetorius}^1, \ \mathbf{Julian}\\ \mathbf{Streitberger}^1, \ \mathbf{Martin}\ \mathbf{Vohral}\mathbf{ik}^3, \end{array}$

Abstract

We study a symmetric second-order linear elliptic PDE discretized by piecewise polynomials of arbitrary degree p > 1. To treat the arising linear system, we propose a geometric multigrid method with zero pre- and one post-smoothing by an overlapping Schwarz (block Jacobi) method [Miraci, Papež, Vohralík. SIAM J. Sci. Comput. 2021]. Introducing optimal step sizes which minimize the algebraic error in the level-wise error correction step of multigrid, one obtains an explicit Pythagorean formula for the algebraic error. Importantly, this inherently induces a fully computable a posteriori estimator for the energy norm of the algebraic error. We show the two following results and their equivalence: 1) the solver contracts the algebraic error independently of the polynomial degree p; 2) the estimator represents a two-sided p-robust bound on the algebraic error. The p-robustness results are obtained by carefully applying the results of [Schöberl, Melenk, Pechstein, Zaglmayr. IMA J. Numer. Anal. 2008 for one mesh, combined with a multilevel stable decomposition for piecewise affine polynomials of [Chen, Nochetto, Xu. Numerical. Math. 2012]. Two adaptive variants of this approach are also presented: a multigrid solver with an adaptive number of smoothing steps per level and a multigrid solver with adaptive local smoothing per patches. Moreover, recent developments in [Miraçi, Praetorius, Streitberger. In preparation] allow to prove that a local variant of the solver is robust also with respect to the number of mesh levels used for rate-optimal adaptive finite element method. Finally, we present a variety of numerical tests to confirm the theoretical results and to illustrate the advantages of our approach.

¹Technische Universität Wien ²Czech Academy of Sciences ³Inria Paris